

DESCRIPTION

Military Grade Olive Drab Duct Tape. High tensile strength for difficult applications. Moisture, solvent, and abrasion resistant. Aggressive adhesion. Conformable with crisp, straight tear for easy handling. Custom slit to width.

APPLICATION PROCESS

Waterproof packaging for military and aerospace applications. Media blast protection and surface masking. Challenging repair, bundling, seaming, patching, and bonding applications. Features include PE-Coated Cloth Backing and Natural Rubber Based Adhesive. High tensile strength for difficult applications. Extremely conformable, Crisp, straight tear. Moisture, solvent and abrasion resistant.

MATERIAL DESCRIPTION

SIZE (width x length)	55 yd
COLOR	Olive Drab
ADHESIVE TYPE	Pressure-Sensitive Tape
CONSTRUCTION	Single Coated
SELF WOUND	Yes
RELEASE LINER MATERIAL	N/A
RELEASE LINER THICKNESS	
WEIGHT	

TECHNICAL DATA

ADHESIVE LAYER	Rubber
BACKING/CARRIER MATERIAL	PE Coated Cloth
BACKING/ADHESIVE THICKNESS	N/A
TOTAL THICKNESS	12.0 mil ASTM D-1000
ADHESION TO STEEL	90 oz/in PSTC-101
TENSILE STRENGTH	50 lb/in ASTM D-1000
ELONGATION	13%
TEMPERATURE APPLICATION	N/A
TEMPERATURE OPERATING	40° to 200°F

Physical and performance characteristics shown are obtained from tests recommended by vendor. Quality Assurance and Technical Service Departments do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Surfaces to be bonded to should be dry, clean and free from oil and grease.

Typical shelf life is one (1) year from date of manufacture (DOM). Recommended storage conditions: 40-60% Humidity, 60°F to 80°F

Note: The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine the product suitability before adapting for commercial use.



195 Polk Avenue • Nashville, Tennessee 37210
p: 615.255.1775 • f: 615.256.6557 • 800.643.5996
can-dotape.com