


## **Premium Gaffer's Tape**



Backing: Matte-Finish Vinyl Coated Cloth

Adhesive: Rubber

Liner: N/A

Colors: Black, White, Gray, Brown, Red, Burgundy,

> Yellow, Dk Green, Beige, Navy, Ral Yellow, Neon Green, Neon Orange, Neon Yellow, Neon Pink, Neon Blue, Royal Blue, Purple, Teal

**Specifications:** Tested in accordance with UL 723

**Standard Sizes:** 48mm x 50m, 72mm x 50m

## **Applications**

- Protect and anchor wiring in the photography Wrapping or bundling wire, metals, and plastics and film industry, convention, and hospitality • Color Coding
- Place marking/spike tape
- Glow in the Dark available for stage safety uses to mark stairs and entryways

- General repair
- Bookbinding
- Vinyl seat repair

## **Features Benefits**

<ul> <li>Heavy-duty vinyl coated cloth backing</li> </ul>	<ul> <li>Matte-finish for less reflectivity and low sheen</li> </ul>
	<ul> <li>Excellent durability and conformability</li> </ul>
<ul> <li>Natural rubber based adhesive</li> </ul>	<ul> <li>High tack for a variety of surfaces</li> </ul>
	<ul> <li>Clean removal - no residue</li> </ul>
Low VOC Content	<ul> <li>Can contribute toward satisfying EQ Credit 4.1</li> </ul>
	(Low Emitting Materials) under LEED®

## **Typical Test Values**

	Standar	Standard UOM M		UOM	Test Method
Total Thickness	11.5	mils	0.292	mm	ASTM D-1000
Adhesion to Steel	50	oz/in	5.47	N/cm	PSTC-101
Adhesion to Backing	29	oz/in	3.17	N/cm	PSTC-101
Tensile Strength	42	lb/in	73.55	N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F		4 to 93 °C		
Smoke Developed	10				
Flame Spread	30				
VOC Content	<1 (	g/L			

Recommended Storage Conditions: 32-90 °F at 50% RH  $\pm$  2% Standard Shelf Life (at 25 °C): 12 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility

